


RM 500

| | |
|---------------------|--|
| TIRE SIZE | 600/65 R 28 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | MOISSONNEUSE |
| VERSION | STEEL BELTED |
| TIRE TYPE | TL |
| LI/SS | 177 A8 ; 165 A8 |



DIMENSIONS US STANDARD

| | | | |
|-----------------|----------|----------------|-----------------|
| CODE USA | 94070961 | RC (IN) | 170.9 |
| SW (IN) | 23.2 | RIM REC | W 18 L |
| OD (IN) | 58.5 | RIM ALT | W 20 L |
| SLR (IN) | 25.2 | ECE | E11-106R-007699 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 12 | 16 | 17 | 23 | 29 | 35 | 41 |
|------------------------|------|------|------|-------|-------|-------|-------|
| 25 FREE ROLLING | 6770 | 7730 | 8700 | 10630 | 12230 | 14160 | 16090 |
| 25 DRIVE WHEEL | 4770 | 5460 | 6140 | 7500 | 8630 | 10000 | 11350 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.