


AGRIMAX SPARGO

TIRE SIZE	VF 480/95 R 54
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	TRACTEUR
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	180 D



DIMENSIONS US STANDARD

CODE USA	94514953	RC (IN)	273.9
SW (IN)	20.0	RIM REC	DW 16 L
OD (IN)	90.6	RIM ALT	DW 15 L
SLR (IN)	40.7	ECE	E11-106R-0011499

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	14	17	20	23	26	29	32	35	46
45	9310	10440	11590	12720	13380	14030	14430	14840	16310
FROM 40 TO 25	10060	11290	12530	13760	14470	15170	15610	16050	17640
20	10270	11520	12780	14040	14760	15480	15930	16380	17990
12	10470	11740	13030	14310	15050	15790	16240	16700	18350
5	11070	12430	13780	15140	15920	16690	17180	17660	19400
UPTO 10 CYC.	13630	15300	16980	18660	19600	20560	21160	21750	23900
UPTO 20 CYC.	11420	12820	14220	15620	16430	17220	17730	18230	20020

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.