

AS 504

TIRE SIZE	15.0/55 - 17
UM	IS STANDARD
CONSTRUCTION	⊠ BIAS
MACHINERY	ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК / ПРИЦЕП ДЛЯ ПОЛЕВЫХ РАБОТ / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК
VERSION	STANDARD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	128 A8
LI/SS FREE ROLLING	141 A8



РАЗМЕРЫ IS STANDARD

SW (MM)	380	RIM REC	13.00
OD (MM)	890	RIM ALT	13
SLR (MM)	395	ECE	E4-106R-001572
RC (MM)	2608	PR	14

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	3.60
10 FR	3605
25 FR	3065
30 FR	2885
40 FR	2575
10 DW	2520
25 DW	2140
30 DW	2010
40 DW	1800

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.