


# AGRIMAX FORCE



<b>TYRE SIZE</b>	<b>IF 650/75 R 38</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	HIGH-POWER TRACTOR / TRACTOR
<b>VERSION</b>	STANDARD
<b>TYRE TYPE</b>	TL
<b>LI/SS</b>	175 D

## DIMENSIONS IS STANDARD

<b>SW (MM)</b>	651	<b>RIM REC</b>	DW 23 B
<b>OD (MM)</b>	1941	<b>RIM ALT</b>	DW 21 B
<b>SLR (MM)</b>	866	<b>ECE</b>	E11-106R-007385
<b>RC (MM)</b>	5802	<b>SRI</b>	925

## LOAD CAPACITY (KG/TYRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
<b>70</b>	2955	3395	3895	4400	4900	5405	5905	6280
<b>FROM 65 TO 40</b>	3245	3730	4280	4830	5385	5935	6490	6900
<b>30</b>	3375	3880	4455	5030	5605	6175	6750	7180
<b>20</b>	3505	4030	4625	5220	5815	6415	7010	7455
<b>10</b>	4120	4735	5435	6140	6840	7540	8240	8765
<b>UPTO 30 CYC</b>	4220	4845	5565	6280	7000	7715	8435	8970
<b>UPTO 15 CYC</b>	5030	5780	6635	7490	8345	9200	10055	10695
<b>UPTO 10 CYC</b>	5515	6335	7275	8215	9150	10090	11030	11730
<b>10 HT</b>	3375	3880	4455	5030	5605	6175	6750	7180

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.