


# RIDEMAX FL 693 M



<b>TIRE SIZE</b>	500/60 R 22.5
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TANKBIL / SLÄPVAGN / ARBETSFORDON
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	155 D ; 152 E

## DIMENSIONER IS STANDARD

<b>SW (MM)</b>	503	<b>RIM REC</b>	AG 16.00
<b>OD (MM)</b>	1172	<b>RIM ALT</b>	15.00; 17.00
<b>SLR (MM)</b>	531	<b>ECE</b>	E4-106R-001402
<b>RC (MM)</b>	3577	<b>SRI</b>	550

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.0	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0
70	1320	1495	1775	2095	2400	2665	2985	3270	3550
65	1435	1630	1940	2290	2620	2910	3255	3565	3875
50	1740	1970	2345	2770	3170	3520	3940	4315	4690
40	1955	2215	2635	3110	3560	3955	4430	4850	5270
25	2270	2575	3065	3615	4135	4595	5145	5635	6125
10	2585	2930	3490	4120	4710	5235	5860	6420	6975

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.