

AGRIMAX FORCE

TIRE SIZE	IF 650/65 R 34
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	КОМБАЙН / ТРАКТОР ВЫСОКОЙ МОЩНОСТИ / ТРАКТОР-ТЯГАЧ
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	161 D



РАЗМЕРЫ IS STANDARD

SW (MM)	650	RIM REC	DW 23 B
OD (MM)	1710	RIM ALT	DW 20 B
SLR (MM)	764	ECE	E4-106R-001826
RC (MM)	5078	SRI	825

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6
70	2355	2775	3150	3535	3870	4205
FROM 65 TO 40	2590	3050	3465	3885	1255	4625
30	2690	3170	3600	4040	4425	4810
20	2795	3290	3740	4195	4595	4995
10	3285	3870	4850	5435	5955	6475
UPTO 30 CYC	3365	3965	4500	5050	5530	6010
UPTO 15 CYC	4010	4725	5370	6020	6595	7165
UPTO 10 CYC	4400	5185	5890	6600	7230	7860
10HT	2690	3170	3600	4040	4425	4810

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.