


# AGRIMAX RT 855

	<b>280/85 R 20</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	ILAÇLAMA / ÜZÜM HASAT MAKINESİ / TRAKTÖR / BIÇERDÖVER / UYGULAMALI MAKINE
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
	112 A8/B



## UNDEFINED IS STANDARD

<b>SW (MM)</b>	292	<b>RIM REC</b>	W 10
<b>OD (MM)</b>	984	<b>RIM ALT</b>	W 9
<b>SLR (MM)</b>	441	<b>ECE</b>	E4-106R-000642
<b>RC (MM)</b>	2952	<b>SRI</b>	475

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6
50	620	720	820	920	1020	1120
40	620	720	820	920	1020	1120
30	660	770	880	985	1095	1200
10 LT	830	965	1100	1235	1370	1505
10 HT	660	770	880	985	1095	1200

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.