

# AW 909

<b>TIRE SIZE</b>	10.0/75 - 12
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	❖ BIAS
<b>MACHINERY</b>	ПРЕСС-ПОДБОРЩИК / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ПРИЦЕП / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS FREE ROLLING</b>	116 A8



## РАЗМЕРЫ US STANDARD

<b>USA CODE</b>	94044870	<b>RC (IN)</b>	81.9
<b>SW (IN)</b>	10.4	<b>RIM REC</b>	9.00
<b>OD (IN)</b>	28.0	<b>RIM ALT</b>	7.0
<b>SLR (IN)</b>	12.3	<b>ECE</b>	E11-106R-005258

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	45
5 FR	3860
15 FR	3280
20 FR	3090
25 FR	2760

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.