

# TF 9090

|                     |                                       |
|---------------------|---------------------------------------|
| <b>TIRE SIZE</b>    | <b>4.00 - 12</b>                      |
| <b>UM</b>           | US STANDARD                           |
| <b>CONSTRUCTION</b> | BIAS                                  |
| <b>MACHINERY</b>    | LITEN TRAKTOR / TRAKTOR /<br>SLÄPVAGN |
| <b>VERSION</b>      | STANDARD                              |
| <b>TIRE TYPE</b>    | TT                                    |
| <b>LI/SS</b>        | 60 A8                                 |



## DIMENSIONER US STANDARD

|                 |          |                |                |
|-----------------|----------|----------------|----------------|
| <b>USA CODE</b> | 94035113 | <b>RC (IN)</b> | 61.9           |
| <b>SW (IN)</b>  | 4.4      | <b>RIM REC</b> | 3.00 D         |
| <b>OD (IN)</b>  | 20.9     | <b>RIM ALT</b> | 2.50 C         |
| <b>SLR (IN)</b> | 10.0     | <b>ECE</b>     | E4-106R-002182 |

## LOAD CAPACITY (LBS/TIRE)

|                  |           |
|------------------|-----------|
| <b>MPH / PSI</b> | <b>74</b> |
| 25               | 550       |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.