


RIB 713

| | |
|---------------------|--|
| TIRE SIZE | IF 280/70 R 15 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | ATTREZZI AGRICOLI / ATTREZZI AGRICOLI |
| VERSIONE | STUBBLE RESISTANT |
| TIRE TYPE | TL |
| LI/SS | 128 D |



DIMENSIONI IS STANDARD

| | | | |
|-----------------|------|-----------------|----------------|
| SW (MM) | 279 | RIM REC | W 8 |
| OD (MM) | 779 | ECE | E4-106R-001820 |
| SLR (MM) | 347 | SRI | 360 |
| RC (MM) | 2356 | TRA CODE | I1 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.6 | 0.8 | 1.0 | 1.2 | 1.4 | 1.6 | 2.0 | 2.4 | 2.8 | 3.2 | 3.6 |
|--------------------|-----|-----|-----|------|------|------|------|------|------|------|------|
| FROM 10 TO 65 KM/H | 670 | 775 | 885 | 1010 | 1120 | 1225 | 1335 | 1425 | 1570 | 1695 | 1800 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.