

AGRIMAX RT 955

TIRE SIZE	340/85 R 48
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	ОПРЫСКИВАТЕЛЬ / КОМБАЙН ДЛЯ УБОРКИ ВИНОГРАДА / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	152 A8/B



РАЗМЕРЫ IS STANDARD

SW (MM)	353	RIM REC	W 12
OD (MM)	1797	RIM ALT	W 11
SLR (MM)	855	ECE	E4-106R-000800
RC (MM)	5572	SRI	875

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.8	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0	4.4
50	1385	1815	2205	2415	2560	2805	3055	3305	3550	-
40	1385	1815	2205	2415	2560	2805	3055	3305	3550	-
30	1485	1940	2360	2585	2740	3005	3270	3535	3800	-
10	1655	2080	2560	3040	3515	3625	4050	4475	4900	5325

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.