

# AGRIMAX RT 855

<b>TIRE SIZE</b>	<b>320/85 R 28</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	ОПРЫСКИВАТЕЛЬ / КОМБАЙН ДЛЯ УБОРКИ ВИНОГРАДА / ТРАКТОР-ТЯГАЧ / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ
<b>VERSION</b>	SPECIAL
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	124 A8/B



## РАЗМЕРЫ US STANDARD

<b>USA CODE</b>	94047352	<b>RC (IN)</b>	147.4
<b>SW (IN)</b>	13.0	<b>RIM REC</b>	W 11
<b>OD (IN)</b>	49.4	<b>RIM ALT</b>	W 9; W 10
<b>SLR (IN)</b>	22.4	<b>ECE</b>	E4-106R-000615

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23
<b>30</b>	1940	2260	2580	2900	3220	3520
<b>25</b>	1940	2260	2580	2900	3220	3520
<b>20</b>	2080	2420	2770	3110	3450	3780
<b>5 LT</b>	2600	3030	3460	3880	4310	4730
<b>5 HT</b>	2080	2420	2770	3110	3450	3780

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.