


RIDEMAX FROST

TYRE SIZE	440/80 R 28 IND
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	TRACTOR
VERSION	STEEL BELTED
TYRE TYPE	TL
LI/SS	156 A8 ; 151 D



DIMENSIONS IS STANDARD

SW (MM)	441	RIM REC	DW 14 L
OD (MM)	1419	RIM ALT	DW 15 L
SLR (MM)	642	ECE	E11-106R-0010949
RC (MM)	4296	SRI	675

LOAD CAPACITY (KG/TYRE)

KM/H / BAR	0.8	1.2	1.6	2	2.4	2.6	2.8	3	3.2
65	1520	2005	2415	2660	2830	2970	3105	3280	3450
50	1645	2165	2615	2875	3060	3210	3360	3545	3730
40	1760	2320	2800	3080	3280	3440	3600	3800	4000
30	1825	2405	2900	3190	3395	3565	3730	3935	4140
20	1915	2525	3045	3350	3570	3745	3915	4135	4350
10	2190	2885	3480	3830	4080	4275	4475	4725	4970
5	2540	3345	4040	4440	4730	4960	5190	5480	5765

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.