


AGRIMAX FORCE

| | |
|--------------|--|
| TIRE SIZE | IF 900/60 R 42 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | MIETITREBBIA / TRATTORE A ELEVATA POTENZA / TRATTORE |
| VERSIONE | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 186 D |



DIMENSIONI IS STANDARD

| | | | |
|----------|------|---------|-----------------|
| SW (MM) | 916 | RIM REC | DW 30 B |
| OD (MM) | 2147 | RIM ALT | TW 30 B |
| SLR (MM) | 950 | ECE | E11-106R-006494 |
| RC (MM) | 6416 | SRI | 1025 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.6 | 0.8 | 1.0 | 1.2 | 1.4 | 1.6 | 2.0 | 2.4 |
|---------------|------|------|------|-------|-------|-------|-------|-------|
| 70 | 3975 | 4580 | 5270 | 5875 | 6570 | 7175 | 8035 | 8645 |
| FROM 65 TO 40 | 4370 | 5035 | 5795 | 6460 | 7220 | 7885 | 8835 | 9500 |
| 30 | 4540 | 5235 | 6025 | 6715 | 7505 | 8200 | 9185 | 9880 |
| 20 | 4715 | 5435 | 6255 | 6975 | 7795 | 8515 | 9540 | 10260 |
| 10 | 5545 | 6390 | 7355 | 8200 | 9165 | 10010 | 11220 | 12065 |
| UPTO 30 CYC | 5680 | 6545 | 7530 | 8395 | 9385 | 10250 | 11485 | 12350 |
| UPTO 15 CYC | 6770 | 7800 | 8980 | 10010 | 11190 | 12220 | 13690 | 14725 |
| UPTO 10 CYC | 7425 | 8555 | 9850 | 10980 | 12270 | 13400 | 15015 | 16150 |
| 10HT | 4540 | 5235 | 6025 | 6715 | 7505 | 8200 | 9185 | 9880 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.