

AS 504

TIRE SIZE	7.50 - 18
UM	IS STANDARD
CONSTRUCTION	⊠ BIAS
MACHINERY	ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК / ПРИЦЕП ДЛЯ ПОЛЕВЫХ РАБОТ / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК
VERSION	STANDARD
TIRE TYPE	TT
LI/SS DRIVE WHEEL	101 A8
LI/SS FREE ROLLING	114 A8



РАЗМЕРЫ IS STANDARD

SW (MM)	209	RIM REC	5.50 F
OD (MM)	854	RIM ALT	4.50 E; 6.00 F; 5.00 F
SLR (MM)	407	ECE	E4-106R-002638
RC (MM)	2649	PR	8

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	3.10
10 FR	1650
25 FR	1405
30 FR	1320
40 FR	1180
10 DW	1155
25 DW	980
30 DW	925
40 DW	825

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.