

MULTIMAX MP 513

| | |
|---------------------|--|
| TIRE SIZE | 425/75 R 20 MPT |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | VEICOLO UNIVERSALE / AUTOCARRO PER FERTILIZZANTI / VEICOLO UNIVERSALE |
| VERSIONE | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 148 G |



DIMENSIONI IS STANDARD

| | | | |
|-----------------|-------|----------------|--------------------------------|
| SW (MM) | 421 | RIM REC | 13 |
| OD (MM) | 1146 | RIM ALT | 13 SDC; 11 SDC; 12 SDC; 11; 12 |
| SLR (MM) | 518.5 | ECE | E11-54R-0016141 |
| RC (MM) | 3465 | | |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 1.6 | 2.0 | 2.5 | 3.0 | 3.5 | 4.0 |
|------------|------|------|------|------|------|------|
| 90 | 1540 | 1810 | 2150 | 2490 | 2820 | 3150 |
| 65 | 1675 | 1965 | 2335 | 2705 | 3060 | 3420 |
| 40 | 1775 | 2085 | 2475 | 2865 | 3245 | 3625 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.