


# MULTIMAX MP 569



|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>445/70 R 19.5</b>   |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | CHARGEUSE TÉLESCOPIQUE /<br>PELLETEUSE   |
| <b>VERSION</b>      | STANDARD   |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 173 A8 ; 180 A2  |

## DIMENSIONS US STANDARD

|                 |          |                |                  |
|-----------------|----------|----------------|------------------|
| <b>CODE USA</b> | 94514380 | <b>RIM REC</b> | 14.00            |
| <b>OD (IN)</b>  | 43.8     | <b>ECE</b>     | E11-106R-0011615 |
| <b>SLR (IN)</b> | 19.6     |                |                  |
| <b>RC (IN)</b>  | 132.4    |                |                  |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 109   |
|-----------|-------|
| 5         | 17600 |
| 25        | 14330 |
| MPH / PSI | 12    |
| 45        | 3350  |
| 30        | 3630  |
| 25        | 3880  |
| 20        | 4020  |
| 10        | 4220  |
| 5         | 4830  |
| 3         | 5600  |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.