


BK-LOADER 53

| | |
|---------------------|--|
| TIRE SIZE | 405/70 R 18 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | CARREGADORA |
| VERSÃO | ARAMID BELTED |
| TIRE TYPE | TL |
| LI/SS | 153A2/149A4 |



DIMENSÕES US STANDARD

| | | | |
|-------------------|----------|----------------|-----------------------|
| CÓDIGO USA | 94069705 | RIM ALT | 14; 13 SDC; 12;12 SDC |
| SW (IN) | 16.0 | | |
| OD (IN) | 41.1 | | |
| RIM REC | 13 | | |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 22 | 29 | 36 | 44 | 51 | 58 | 65 | 73 | 80 |
|-----------|------|------|------|------|------|------|-------|-------|-------|
| 12 | 2520 | 3230 | 3810 | 4380 | 5020 | 5530 | 6100 | 6600 | 7170 |
| 5 | 2830 | 3630 | 4270 | 4920 | 5640 | 6210 | 6850 | 7410 | 8050 |
| STATIC | 4520 | 5810 | 6850 | 7880 | 9030 | 9940 | 10970 | 11880 | 12900 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.