

# AGRIMAX TURF RT 333

<b>TIRE SIZE</b>	<b>340/85 R 28</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	VENDIMIADORA / MAQUINA PARA LA RECOGIDA DE FRUTA / MINITRACTOR / TRACTOR / COSECHADORA
<b>VERSIÓN</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	127 A8 ; 127 B



## DIMENSIONES US STANDARD

<b>CÓDIGO USA</b>	94076390	<b>RC (IN)</b>	152.5
<b>SW (IN)</b>	14.6	<b>RIM REC</b>	W 12
<b>OD (IN)</b>	50.7	<b>RIM ALT</b>	W11;DW11;DW12
<b>SLR (IN)</b>	23.0	<b>ECE</b>	E11-106R-0010343

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23
30	2130	2470	2830	3170	3520	3860
25	2130	2470	2830	3170	3520	3860
20	2290	2650	3030	3400	3770	4140
5 LT	2850	3320	3790	4250	4710	5170
5 HT	2290	2650	3030	3400	3770	4140

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.