

# TRAC GRADER +

|                     |                   |
|---------------------|-------------------|
| <b>TIRE SIZE</b>    | <b>13.00 - 24</b> |
| <b>UM</b>           | US STANDARD       |
| <b>CONSTRUCTION</b> | ⊠ BIAS            |
| <b>MACHINERY</b>    | NIVELEUSE         |
| <b>VERSION</b>      | SPECIAL           |
| <b>TIRE TYPE</b>    | TL                |



## DIMENSIONS US STANDARD

|                 |          |                 |                             |
|-----------------|----------|-----------------|-----------------------------|
| <b>CODE USA</b> | 94014668 | <b>RIM REC</b>  | 8.00 TG SDC                 |
| <b>OD (IN)</b>  | 50.4     | <b>RIM ALT</b>  | 9.00/1.5 (DC); 10.00/VA SDC |
| <b>SLR (IN)</b> | 23.6     | <b>PR</b>       | 12                          |
| <b>RC (IN)</b>  | 155.2    | <b>TRA CODE</b> | G2                          |

## LOAD CAPACITY (LBS/TIRE)

|                  |           |
|------------------|-----------|
| <b>MPH / PSI</b> | <b>44</b> |
| 25               | 6000      |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.