


# AGRIMAX TERIS

<b>TIRE SIZE</b>	<b>900/60 R 32 CHO</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	CEIFEIRA / COLHEDORA DE ALGODÃO
<b>VERSÃO</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	185 A8 ; 182 B



## DIMENSÕES US STANDARD

<b>CÓDIGO USA</b>	94040865	<b>RC (IN)</b>	227.4
<b>SW (IN)</b>	34.4	<b>RIM REC</b>	DW 27 B
<b>OD (IN)</b>	75.2	<b>RIM ALT</b>	DW 28 B; DW 30 B
<b>SLR (IN)</b>	34.4	<b>ECE</b>	E4-106R-001433

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	12	15	20	23	29	35	41	46	52	58
<b>30</b>	7440	8430	10580	11740	13060	14050	15380	16530	17610	18740
<b>25</b>	8190	9280	11640	12920	14370	15460	16920	18190	19170	20390
<b>20</b>	8760	9930	12470	13820	15390	16560	18110	19470	20510	21820
<b>10 CYC</b>	13510	15310	19210	21320	23720	25520	27920	30010	31630	33650
<b>5 CYC</b>	14740	16700	20950	23250	25870	27830	30460	32740	34510	36700

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.