


# AS 504

<b>TYRE SIZE</b>	<b>24X8.50 - 12</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 BIAS
<b>MACHINERY</b>	TELEHANDLER / FIELD TRAILER / IMPLEMENTS / TELEHANDLER
<b>VERSION</b>	STANDARD
<b>TYRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	81 A8
<b>LI/SS FREE ROLLING</b>	94 A8



## DIMENSIONS US STANDARD

<b>USA CODE</b>	94512409	<b>RC (IN)</b>	69.3
<b>SW (IN)</b>	8.5	<b>RIM REC</b>	7 JA; 7.00 I
<b>OD (IN)</b>	24.0	<b>ECE</b>	E11-106R-0010452
<b>SLR (IN)</b>	11.2	<b>PR</b>	6

## LOAD CAPACITY (LBS/TYRE)

MPH / PSI	74
5 FR	2070
15 FR	1750
20 FR	1650
25 FR	1480
5 DW	1420
15 DW	1215
20 DW	1140
25 DW	1020

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.