


AW 09

| | |
|---------------------------|--|
| TIRE SIZE | 260/70 - 15.3 |
| UM | IS STANDARD |
| CONSTRUCTION |  BIAS |
| MACHINERY | BALER / IMPLEMENT MACHINERY / TRAILER / HAY HARVESTER / IMPLEMENTS / HARVESTER |
| VERSION | STANDARD |
| TL/TT | TL |
| LI/SS DRIVE WHEEL | 114 A8 |
| LI/SS FREE ROLLING | 126 A8 |



DIMENSIONS IS STANDARD

| | | | |
|-----------------|------|----------------|----------------|
| SW (MM) | 268 | RIM REC | 9.00 |
| OD (MM) | 753 | ECE | E4-106R-000373 |
| SLR (MM) | 335 | | |
| RC (MM) | 2206 | | |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 3.60 |
|------------|------|
| 10 FR | 2380 |
| 25 FR | 2025 |
| 30 FR | 1905 |
| 40 FR | 1700 |
| 10 DW | 1650 |
| 25 DW | 1405 |
| 30 DW | 1320 |
| 40 DW | 1180 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.