


# AW 702

<b>TIRE SIZE</b>	<b>10.0/75 - 15.3</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 BIAS
<b>MACHINERY</b>	ПРЕСС-ПОДБОРЩИК / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ПРИЦЕП / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ПРИЦЕП
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS FREE ROLLING</b>	126 A8



## РАЗМЕРЫ US STANDARD

<b>USA CODE</b>	94009077	<b>RC (IN)</b>	87.1
<b>SW (IN)</b>	10.8	<b>RIM REC</b>	9.00
<b>OD (IN)</b>	29.9	<b>ECE</b>	E4-106R-001541
<b>SLR (IN)</b>	13.8	<b>PR</b>	12

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	68
5 FR	5250
15 FR	4460
20 FR	4200
25 FR	3750

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.