

RIDEMAX FL 615

TIRE SIZE	VF 900/65 R 38
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	ПРИЦЕП / АВТОЦИСТЕРНА / РАЗБРАСЫВАТЕЛЬ / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ
VERSION	STEEL BELTED
TIRE TYPE	TL
LI/SS	200 D



РАЗМЕРЫ US STANDARD

USA CODE	94515349	RC (IN)	253.7
SW (IN)	35.1	RIM REC	DW 30 B
OD (IN)	83.3	ECE	E11-106R-0011504
SLR (IN)	36.6		

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	15	17	23	29	35	41
40	15120	16970	20680	23460	27160	30860
30	17700	19860	24190	27450	31780	36110
25	19510	21900	26690	30270	35040	39810
20	21330	23940	29170	33080	38300	43520
15	22090	24790	30190	34250	39660	45060
10	22990	25800	31440	35660	41290	46910
5	24810	27840	33920	38470	44540	50620

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.