



## DATA SHEET

PRINTED ON  
23-04-2026

# AIROMAX AM 27

|                     |                                                                                          |
|---------------------|------------------------------------------------------------------------------------------|
| <b>TIRE SIZE</b>    | <b>445/95 R 25</b>                                                                       |
| <b>UM</b>           | US STANDARD                                                                              |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | MOBILE CRANE                                                                             |
| <b>VERSION</b>      | STANDARD                                                                                 |
| <b>TIRE TYPE</b>    | TL                                                                                       |
| <b>LI/SS</b>        | 174 F                                                                                    |



### DIMENSIONS US STANDARD

|                 |          |                |                            |
|-----------------|----------|----------------|----------------------------|
| <b>USA CODE</b> | 94039043 | <b>RIM REC</b> | 11.25/2.0                  |
| <b>OD (IN)</b>  | 58.7     | <b>RIM ALT</b> | 11.00/1.7 CR; 11.00/1.7CRL |
| <b>SLR (IN)</b> | 27.4     | <b>ECE</b>     | E4-54R-0028867             |
| <b>RC (IN)</b>  | 180.6    |                |                            |

### LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 130   |
|-----------|-------|
| 20        | 18700 |
| 25        | 17100 |
| 30        | 16500 |
| 35        | 16100 |
| 43        | 15700 |
| 50        | 14800 |
| 55        | 13900 |
| 62        | 12300 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.