


MULTIMAX MP 527

TIRE SIZE	340/80 R 20 IND
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	CHARGEUSE COMPACTE / CHARGEUSE TÉLESCOPIQUE / CHARGEUSE COMPACTE / CHARGEUSE TÉLESCOPIQUE
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	144 A8/B



DIMENSIONS IS STANDARD

SW (MM)	343	RIM REC	11
OD (MM)	1052	RIM ALT	W10 ; 11 SDC ; W11 ; 12 ; 12 SDC
SLR (MM)	483	ECE	E11-106R-003957
RC (MM)	3176	SRI	500

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.6	2.0	2.4	2.8	3.2	3.5	4.0	4.2	4.4
50	1345	1600	1820	2075	2325	2495	2800	-	-
40	1345	1600	1820	2075	2325	2495	2800	-	-
30	1440	1710	1950	2220	2490	2670	3000	-	-
25	1495	1775	2025	2305	2585	2770	3110	-	-
10 CYC.	1640	2020	2375	2730	3110	3385	3825	4035	4200
STATIC	2515	3095	3640	4190	4770	5185	5865	6185	6440

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.