


# AGRIMAX ELOS

<b>TIRE SIZE</b>	<b>480/70 R 34</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TRACTOR
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	155 A8 ; 155 B



## ABMESSUNGEN IS STANDARD

<b>SW (MM)</b>	500	<b>RIM REC</b>	W 15 L
<b>OD (MM)</b>	1605	<b>RIM ALT</b>	W 16 L ; W 14 L
<b>SLR (MM)</b>	733	<b>ECE</b>	E11-106R-007532
<b>RC (MM)</b>	4868	<b>SRI</b>	750

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4	2.8	3.2
<b>50</b>	1515	1785	2055	2290	2560	2790	3065	3375	3645	3875
<b>40</b>	1515	1785	2055	2290	2560	2790	3065	3375	3645	3875
<b>30</b>	1620	1910	2200	2450	2740	2990	3280	3615	3905	4150
<b>10 LT</b>	2030	2390	2755	3070	3430	3745	4105	4520	4885	5195
<b>10 HT</b>	1620	1910	2200	2450	2740	2990	3280	3615	3905	4150

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.