


AT 621

| | |
|---------------------------|--|
| TIRE SIZE | 12.5/80 - 18 |
| UM | IS STANDARD |
| CONSTRUCTION |  BIAS |
| MACHINERY | CARGADORA COMPACTA / CARGADORA RETROEXCAVADORA / CARGADORA RETROEXCAVADORA / PALA CARGADORA |
| VERSIÓN | STANDARD |
| TIRE TYPE | TT |
| LI/SS DRIVE WHEEL | 135 A8 |
| LI/SS FREE ROLLING | 148 A8 |



DIMENSIONES IS STANDARD

| | | | |
|-----------------|------|----------------|-----------------|
| SW (MM) | 308 | RIM REC | W 9 |
| OD (MM) | 987 | RIM ALT | 11.0 |
| SLR (MM) | 434 | ECE | E11-106R-006957 |
| RC (MM) | 2916 | PR | 16 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 4.90 |
|------------|------|
| 10 FR | 4410 |
| 25 FR | 3750 |
| 30 FR | 3530 |
| 40 FR | 3150 |
| 10 DW | 3050 |
| 25 DW | 2595 |
| 30 DW | 2440 |
| 40 DW | 2180 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.