

MULTIMAX MP 527

| | |
|---------------------|--|
| TIRE SIZE | 400/70 R 24 IND |
| UM | US STANDARD |
| CONSTRUCTION | |
| MACHINERY | COMPACT LOADER / TELEHANDLER / COMPACT LOADER / TELEHANDLER |
| VERSION | STANDARD |
| TL/TT | TL |
| LI/SS | 152 A8/B |



DIMENSIONS US STANDARD

| | | | |
|-----------------|----------|----------------|---|
| USA CODE | 94053483 | RC (IN) | 141.6 |
| SW (IN) | 15.9 | RIM REC | 13 |
| OD (IN) | 46.1 | RIM ALT | DW 12 ; DW 13 ; DW 13 L ; 13 SDC ; DW 14 L |
| SLR (IN) | 21.3 | ECE | E11-106R-003958 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 23 | 29 | 35 | 41 | 46 | 51 | 58 | 61 | 64 |
|-----------|------|------|-------|-------|-------|-------|-------|-------|-------|
| 30 | 3760 | 4460 | 5090 | 5800 | 6500 | 6970 | 7830 | - | - |
| 25 | 3760 | 4460 | 5090 | 5800 | 6500 | 6970 | 7830 | - | - |
| 20 | 4020 | 4780 | 5450 | 6210 | 6960 | 7460 | 8380 | - | - |
| 15 | 4180 | 4960 | 5650 | 6440 | 7220 | 7750 | 8700 | - | - |
| 5 CYC. | 4590 | 5640 | 6640 | 7640 | 8700 | 9460 | 10690 | 11280 | 11740 |
| STATIC | 7020 | 8640 | 10170 | 11710 | 13330 | 14490 | 16390 | 17280 | 18000 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.