


# MULTIMAX MP 522

<b>TIRE SIZE</b>	<b>380/75 R 20 IND</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	COMPACT LOADER / TELEHANDLER / COMPACT LOADER / TELEHANDLER
<b>VERSION</b>	STANDARD
<b>TL/TT</b>	TL
<b>LI/SS</b>	148 A8/B



## DIMENSIONS IS STANDARD

<b>SW (MM)</b>	384	<b>RIM REC</b>	W 12
<b>OD (MM)</b>	1074	<b>RIM ALT</b>	W 11 ; 11 ; 12
<b>SLR (MM)</b>	483	<b>ECE</b>	E11-106R-002963
<b>RC (MM)</b>	3251	<b>SRI</b>	500

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.6	2.0	2.4	2.8	3.2	3.6	3.8	4.0	4.2	4.4
50	1500	1770	2040	2305	2575	2860	3005	3150	-	-
40	1500	1770	2040	2305	2575	2860	3005	3150	-	-
30	1610	1900	2195	2490	2780	3075	3220	3370	-	-
25	1670	1975	2280	2585	2890	3195	3350	3500	-	-
10 CYC.	1850	2260	2670	3080	3490	3900	4110	4315	4520	4730
STATIC	2840	3470	4100	4730	5360	5990	6305	6620	6935	7250

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.