

# FLOTATION 648

<b>TIRE SIZE</b>	<b>600/50 - 22.5</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 BIAS
<b>MACHINERY</b>	EMPACADORA DE HENO / COSECHADORA / ESPARCIDOR / COSECHADORA / MAQUINARIA AGRÍCOLA
<b>VERSIÓN</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	155 A8/151 B
<b>LI/SS FREE ROLLING</b>	167 A8/163 B



## DIMENSIONES IS STANDARD

<b>SW (MM)</b>	611	<b>RIM REC</b>	AG 20.00
<b>OD (MM)</b>	1170	<b>ECE</b>	E4-106R-002275
<b>SLR (MM)</b>	510	<b>PR</b>	18
<b>RC (MM)</b>	3501		

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	2.70	2.80	2.90
10 FR	7315	7475	7630
20 FR	6585	6730	6865
30 FR	5850	5980	6105
40 FR	5225	5340	5450
50 FR	4705	4805	4875
10 DW	5200	5315	5425
20 DW	4680	4780	4885
30 DW	4160	4250	4340
40 DW	3715	3795	3875
50 DW	3345	3415	3450

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.