


# AGRIMAX RT 600

<b>TYRE SIZE</b>	<b>750/70 R 26</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	HARVESTER / SPREADER / TRACTOR / IMPLEMENTS
<b>VERSION</b>	STANDARD
<b>TL/TT</b>	TL
<b>LI/SS</b>	172 A8/B



## DIMENSIONS US STANDARD

<b>USA CODE</b>	94073146	<b>RC (IN)</b>	207.4
<b>SW (IN)</b>	30.7	<b>RIM REC</b>	DW 25 B
<b>OD (IN)</b>	68.9	<b>RIM ALT</b>	DW 24 B
<b>SLR (IN)</b>	30.9	<b>ECE</b>	E11-106R-007934

## LOAD CAPACITY (LBS/TYRE)

MPH / PSI	9	12	15	17	20	23	29	35	41	46	52
30	5970	6940	7930	8900	9780	10840	11950	12640	13890	-	-
25	5970	6940	7930	8900	9780	10840	11950	12640	13890	-	-
20	6400	7440	8490	9520	10570	11610	12800	13550	14880	-	-
5 LT	8010	9310	10630	11930	13230	14540	16030	16950	18630	-	-
5 HT	6400	7440	8490	9520	10570	11610	12800	13550	14880	-	-
5 CYC	-	11170	12730	14290	15850	17420	19200	20310	22320	22670	23610

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.