


AGRIMAXFACTOR

| | |
|---------------------|------------------------------------------------------------------------------------------|
| TIRE SIZE | 480/70 R 34 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | TRATOR |
| VERSÃO | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 149 D ; 152 A8 |



DIMENSÕES IS STANDARD

| | | | |
|-----------------|------|----------------|-----------------|
| SW (MM) | 479 | RIM REC | W 15 L |
| OD (MM) | 1580 | RIM ALT | W 14 L; W 16 L |
| SLR (MM) | 723 | ECE | E11-106R-007642 |
| RC (MM) | 4748 | SRI | 750 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.6 | 0.8 | 1.0 | 1.2 | 1.4 | 1.6 | 2.0 | 2.4 |
|------------|------|------|------|------|------|------|------|------|
| 65 | 1530 | 1755 | 2015 | 2275 | 2535 | 2795 | 3055 | 3250 |
| 50 | 1610 | 1845 | 2120 | 2395 | 2665 | 2940 | 3215 | 3415 |
| 40 | 1675 | 1925 | 2210 | 2495 | 2780 | 3065 | 3350 | 3560 |
| 30 | 1760 | 2020 | 2320 | 2620 | 2920 | 3220 | 3520 | 3740 |
| 10 LT | 2050 | 2355 | 2705 | 3050 | 3400 | 3750 | 4095 | 4355 |
| 10 HT | 1760 | 2020 | 2320 | 2620 | 2920 | 3220 | 3520 | 3740 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.