

# AGRIMAX RT 855

<b>TIRE SIZE</b>	<b>340/85 R 24</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	PULVERIZADOR AGRÍCOLA / VINDIMADORA / TRATOR / CEIFEIRA / IMPLEMENTOS AGRÍCOLAS
<b>VERSÃO</b>	SPECIAL
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	125 A8/B



## DIMENSÕES IS STANDARD

<b>SW (MM)</b>	353	<b>RIM REC</b>	W 12
<b>OD (MM)</b>	1188	<b>RIM ALT</b>	W 11
<b>SLR (MM)</b>	531	<b>ECE</b>	E4-106R-000604
<b>RC (MM)</b>	3540	<b>SRI</b>	575

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6
50	910	1060	1205	1355	1505	1650
40	910	1060	1205	1355	1505	1650
30	975	1135	1295	1455	1615	1770
10 LT	1220	1420	1620	1820	2020	2215
10 HT	975	1135	1295	1455	1615	1770

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.