

# AS 504

|                           |              |
|---------------------------|--------------|
| <b>TYRE SIZE</b>          | 16.5/85 - 24 |
| <b>UM</b>                 | IS STANDARD  |
| <b>CONSTRUCTION</b>       | ⊠ BIAS       |
| <b>MACHINERY</b>          | IMPLEMENTS   |
| <b>VERSION</b>            | STANDARD     |
| <b>TYRE TYPE</b>          | TL           |
| <b>LI/SS DRIVE WHEEL</b>  | 155 A8       |
| <b>LI/SS FREE ROLLING</b> | 168 A8       |



## DIMENSIONS IS STANDARD

|                 |      |                |                |
|-----------------|------|----------------|----------------|
| <b>SW (MM)</b>  | 415  | <b>RIM REC</b> | W 13           |
| <b>OD (MM)</b>  | 1325 | <b>RIM ALT</b> | W 14 L; W 15 L |
| <b>SLR (MM)</b> | 584  | <b>ECE</b>     | E4-106R-001877 |
| <b>RC (MM)</b>  | 4013 | <b>PR</b>      | 16             |

## LOAD CAPACITY (KG/TYRE)

| <b>KM/H / BAR</b> | <b>3.80</b> |
|-------------------|-------------|
| 10 FR             | 7840        |
| 25 FR             | 6665        |
| 30 FR             | 6270        |
| 40 FR             | 5600        |
| 10 DW             | 5425        |
| 25 DW             | 4610        |
| 30 DW             | 4340        |
| 40 DW             | 3875        |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.