


# PL 801

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | 21X8 - 9   |
| <b>UM</b>           | IS STANDARD  |
| <b>CONSTRUCTION</b> |  BIAS                               |
| <b>MACHINERY</b>    | ADAINEUR ROTATIF / MOISSONNEUSE<br>/ CHARIOT ÉLÉVATEUR /<br>MOISSONNEUSE / OUTILLAGE<br>AGRICOLE / CHARIOT ÉLÉVATEUR |
| <b>VERSION</b>      | STANDARD   |
| <b>TIRE TYPE</b>    | TT   |



## DIMENSIONS IS STANDARD

|                |        |            |                 |
|----------------|--------|------------|-----------------|
| <b>SW (MM)</b> | 200    | <b>ECE</b> | E11-106R-003643 |
| <b>OD (MM)</b> | 535    | <b>PR</b>  | 14              |
| <b>RIM REC</b> | 6.00 E |            |                 |
| <b>RIM ALT</b> | 7.00 E |            |                 |

## LOAD CAPACITY (KG/TIRE)

| <b>KM/H / BAR</b>         | <b>9.00</b> |
|---------------------------|-------------|
| <b>25 LOAD WHEEL</b>      | 2535        |
| <b>25 STEER WHEEL</b>     | 1950        |
| <b>10 OTHER VEHICLES</b>  | 2535        |
| <b>25 OTHER VEHICLES</b>  | 1950        |
| <b>STATIC SIDE LOADER</b> | 2945        |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.