


# AGRIMAX V- FLECTO

<b>TIRE SIZE</b>	<b>VF 650/85 R 38</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TRATTORE A ELEVATA POTENZA / TRATTORE
<b>VERSIONE</b>	SPECIAL
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	182 D



## DIMENSIONI IS STANDARD

<b>SW (MM)</b>	670	<b>RIM REC</b>	DW 23 B
<b>OD (MM)</b>	2071	<b>RIM ALT</b>	DW 20 B; DW 21 B
<b>SLR (MM)</b>	887	<b>ECE</b>	E11-106R-0010579
<b>RC (MM)</b>	6119	<b>SRI</b>	975

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0
70	3865	4485	5105	5800	6420	7035	7735
<b>FROM 65 TO 40</b>	4250	4930	5610	6375	7055	7735	8500
30	4335	5025	5720	6500	7195	7885	8670
20	4420	5125	5830	6630	7335	8040	8840
10	4675	5420	6170	7010	7760	8505	9350
<b>UPTO 30 CYC</b>	4820	5590	6365	7230	8005	8775	9645
<b>UPTO 15 CYC</b>	5755	6675	7595	8635	9555	10475	11515
<b>UPTO 10 CYC</b>	6310	7315	8325	9465	10470	11480	12620
10HT	4335	5025	5720	6500	7195	7885	8670

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.