


EARTHMAX SR 484

| | |
|----------------------|--|
| MEDIDA DEL NEUMÁTICO | 27.00 R 49 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | DÚMPER RIGIDO |
| VERSIÓN | HEAT RESISTANT COMPOUND |
| TIRE TYPE | TL |
| LI/SS | 223 B |



DIMENSIONES IS STANDARD

| | | | |
|----------|-----------|------------------------|---------|
| OD (MM) | 2647 | TRA CODE / STAR RATING | E3 / ** |
| SLR (MM) | 1193 | | |
| RC (MM) | 8055 | | |
| RIM REC | 19,50/4.0 | | |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 5.00 | 5.25 | 5.50 | 5.75 | 6.00 | 6.25 | 6.50 | 6.75 | 7.00 |
|------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 50 | 20600 | 21800 | 22400 | 23000 | 23600 | 25000 | 25750 | 26500 | 27250 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.