

FLOTATION 648

TIRE SIZE	850/50 - 30.5
UM	IS STANDARD
CONSTRUCTION	⊗ BIAS
MACHINERY	EMPACADORA DE HENO / COSECHADORA / ESPARCIDOR / COSECHADORA / MAQUINARIA AGRÍCOLA
VERSIÓN	HD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	176 A8/173 B
LI/SS FREE ROLLING	189 A8/185 B



DIMENSIONES IS STANDARD

SW (MM)	850	RIM REC	AG 28.00
OD (MM)	1650	ECE	E11-106R-004566
SLR (MM)	710	PR	18
RC (MM)	4935		

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	2.30	2.40	2.50
10 FR	13735	14075	14420
20 FR	12360	12670	12980
30 FR	10985	11260	11535
40 FR	9810	10055	10300
50 FR	8830	9050	9250
10 DW	9465	9700	9940
20 DW	8520	8730	8945
30 DW	7570	7760	7950
40 DW	6760	6930	7100
50 DW	6085	6235	6500

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.