


# AGRIMAX SPARGO SB

<b>TYRE SIZE</b>	<b>VF 270/95 R 38</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TRACTOR
<b>VERSION</b>	STEEL BELTED
<b>TYRE TYPE</b>	TL
<b>LI/SS</b>	151 D



## DIMENSIONS US STANDARD

<b>USA CODE</b>	94506309	<b>RC (IN)</b>	179.0
<b>SW (IN)</b>	11.0	<b>RIM REC</b>	W9
<b>OD (IN)</b>	58.7	<b>ECE</b>	E11-106R-0010500
<b>SLR (IN)</b>	27.2		

## LOAD CAPACITY (LBS/TYRE)

MPH / PSI	14	17	20	23	29	35	41	46	52	58
45	3270	3680	4090	4440	4920	5200	5680	6170	6590	6930
FROM 40 TO 25	3590	4040	4500	4880	5410	5710	6240	6780	7240	7610
20	3650	4130	4590	4980	5520	5820	6380	6920	7380	7760
12	3730	4200	4680	5080	5630	5950	6500	7060	7530	7920
5	3940	4450	4940	5360	5950	6290	6870	7460	7960	8370

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.