


# AGRIMAX RT 600

|                     |  |
|---------------------|--|
|                     | <b>750/65 R 26</b>   |
| <b>UM</b>           | IS STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | BIÇERDÖVER / YAYICI / TRAKTÖR /<br>UYGULAMALI MAKINE                                     |
| <b>VERSION</b>      | STANDARD   |
| <b>TIRE TYPE</b>    | TL   |
|                     | 171 A8/B   |



## UNDEFINED IS STANDARD

|                 |      |                |                   |
|-----------------|------|----------------|-------------------|
| <b>SW (MM)</b>  | 750  | <b>RIM REC</b> | DW 24 B           |
| <b>OD (MM)</b>  | 1636 | <b>RIM ALT</b> | DW 23 B ; DW 25 B |
| <b>SLR (MM)</b> | 737  | <b>ECE</b>     | E11-106R-006182   |
| <b>RC (MM)</b>  | 4987 | <b>SRI</b>     | 775               |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.8  | 1.0  | 1.2  | 1.4  | 1.6  | 2.0  | 2.4  | 2.8  | 3.2  | 3.4   | 3.8   |
|------------|------|------|------|------|------|------|------|------|------|-------|-------|
| 50         | 2830 | 3260 | 3690 | 4000 | 4370 | 4860 | 5230 | 5720 | 6150 | -     | -     |
| 40         | 2830 | 3260 | 3690 | 4000 | 4370 | 4860 | 5230 | 5720 | 6150 | -     | -     |
| 30         | 3030 | 3495 | 3955 | 4285 | 4680 | 5205 | 5600 | 6125 | 6585 | -     | -     |
| 10 LT      | 3795 | 4370 | 4950 | 5360 | 5855 | 6515 | 7010 | 7670 | 8245 | -     | -     |
| 10 HT      | 3030 | 3495 | 3955 | 4285 | 4680 | 5205 | 5600 | 6125 | 6585 | -     | -     |
| 10 CYC     | -    | 5240 | 5930 | 6425 | 7015 | 7810 | 8400 | 9190 | 9880 | 10010 | 10455 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.