

AS 504

| | |
|---------------------------|---------------------|
| TYRE SIZE | 12.5/80 - 18 |
| UM | US STANDARD |
| CONSTRUCTION | ⊠ BIAS |
| MACHINERY | IMPLEMENTS |
| VERSION | STANDARD |
| TYRE TYPE | TL |
| LI/SS DRIVE WHEEL | 138 A8 |
| LI/SS FREE ROLLING | 150 A8 |



DIMENSIONS US STANDARD

| | | | |
|-----------------|----------|----------------|-----------------|
| USA CODE | 94031252 | RC (IN) | 113.9 |
| SW (IN) | 12.1 | RIM REC | W 9 |
| OD (IN) | 38.9 | RIM ALT | 9; 11 |
| SLR (IN) | 17.2 | ECE | E11-106R-004348 |

LOAD CAPACITY (LBS/TYRE)

| MPH / PSI | 80 |
|-----------|-------|
| 5 FR | 10340 |
| 15 FR | 8780 |
| 20 FR | 8270 |
| 25 FR | 7390 |
| 5 DW | 7290 |
| 15 DW | 6190 |
| 20 DW | 5830 |
| 25 DW | 5200 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.