


# AW 729

<b>TIRE SIZE</b>	<b>500/50 - 17</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 BIAS
<b>MACHINERY</b>	ПРЕСС-ПОДБОРЩИК / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ПРИЦЕП / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	137 A8
<b>LI/SS FREE ROLLING</b>	149 A8



## РАЗМЕРЫ IS STANDARD

<b>SW (MM)</b>	500	<b>RIM REC</b>	16.00
<b>OD (MM)</b>	945	<b>ECE</b>	E11-106R-006616
<b>SLR (MM)</b>	426		
<b>RC (MM)</b>	2885		

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	2.80
10 FR	4550
25 FR	3870
30 FR	3640
40 FR	3250
10 DW	3220
25 DW	2735
30 DW	2575
40 DW	2300

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.