

AGRIMAX RT 765

TIRE SIZE	420/70 R 24
UM	IS STANDARD
MACHINERY	SPRAYER / TRACTOR / VINEYARD HARVESTER / HARVESTER / IMPLEMENTS
VERSION	STANDARD
TL/TT	TL
LI/SS	134 D



DIMENSIONS IS STANDARD

SW (MM)	418	ECE	E11-106R-005825
OD (MM)	1248	SRI	600
SLR (MM)	554	TRA CODE	R1W
RC (MM)	3680	TREAD DEPTH (MM)	43,5
RIM REC	W 13	TKPH (US) (TM/H)	0
RIM ALT	W 12 ; W 14 L		

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0
65	1060	1230	1400	1590	1760	1930	2120
50	1115	1295	1475	1675	1855	2030	2230
40	1165	1350	1535	1745	1930	2120	2325
30	1220	1420	1615	1830	2030	2225	2440
10 LT	1425	1655	1880	2135	2365	2590	2745
10 HT	1220	1420	1615	1830	2030	2225	2440

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.