DATA SHEET

Latest update
3-08-2026

TR 135

TIRE SIZE	**14.9 - 26**
UM	IS STANDARD
MACHINERY	TRACTOR / TRAILER
VERSION	HD
TL/TT	TT
LI/SS	129 A6

DIMENSIONS IS STANDARD

OD (MM)	1315	**RIM ALT**	W 11 ; W 12
SLR (MM)	599	**PR**	8
RC (MM)	3947	**TRA CODE**	R1
RIM REC	W 13	**TREAD DEPTH (MM)**	36

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.80
30	1850

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balkrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.