


# AGRIMAX TURF RT 333

	<b>280/70 R 18</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	ÜZÜM HASAT MAKINESİ / MEYVE HASADI MAKINESİ / KÜÇÜK TRAKTÖR / TRAKTÖR / BIÇERDÖVER
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
	114 A8 ; 114 B



## UNDEFINED IS STANDARD

<b>SW (MM)</b>	289	<b>RIM REC</b>	W 9
<b>OD (MM)</b>	840	<b>RIM ALT</b>	W 8 ; W 10
<b>SLR (MM)</b>	390	<b>ECE</b>	E11-106R-006473
<b>RC (MM)</b>	2550	<b>SRI</b>	400

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
50	555	640	735	830	925	1015	1110	1180
40	555	640	735	830	925	1015	1110	1180
30	595	685	785	890	990	1090	1190	1265
10 LT	745	860	985	1110	1240	1365	1490	1585
10 HT	595	695	785	890	990	1090	1190	1265

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.