


# MULTIMAX MP 513

<b>TIRE SIZE</b>	<b>425/75 R 20 MPT</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	VEHICUL UNIVERSAL / CAMION PENTRU ÎNGRĂȘĂMINTE / VEHICUL UNIVERSAL
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	148 G



## DIMENSIUNI IS STANDARD

<b>SW (MM)</b>	421	<b>RIM REC</b>	13
<b>OD (MM)</b>	1146	<b>RIM ALT</b>	13 SDC; 11 SDC; 12 SDC; 11; 12
<b>SLR (MM)</b>	518.5	<b>ECE</b>	E11-54R-0016141
<b>RC (MM)</b>	3465		

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.6	2.0	2.5	3.0	3.5	4.0
90	1540	1810	2150	2490	2820	3150
65	1675	1965	2335	2705	3060	3420
40	1775	2085	2475	2865	3245	3625

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.