


# AGRIMAX V-FLECTO



<b>TIRE SIZE</b>	<b>VF 540/65 R 28</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	HIGH-POWER TRACTOR / TRACTOR
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	154 D

## DIMENSIONS IS STANDARD

<b>SW (MM)</b>	549	<b>RIM REC</b>	DW 20 B
<b>OD (MM)</b>	1413	<b>RIM ALT</b>	DW 18 L
<b>SLR (MM)</b>	622	<b>ECE</b>	E11-106R-005710
<b>RC (MM)</b>	4160	<b>SRI</b>	675

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6
70	1910	2250	2555	2865	3135	3410
<b>FROM 65 TO 40</b>	2100	2475	2810	3150	3450	3750
30	2140	2520	2865	3210	3515	3825
20	2180	2570	2920	3275	3585	3900
10	2310	2720	3090	3465	3795	4125
<b>*UPTO 10 CYC WITH FRONT LOADER</b>	2940	3465	3930	4410	4830	5250
10 HT	2140	2520	2865	3210	3515	3825

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.