

FL 630 SUPER

TIRE SIZE	710/50 R 30.5
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	ESPARCIDOR / CAMIÓN CISTERNA / REMOLQUE / MAQUINARIA AGRÍCOLA
VERSIÓN	STEEL BELTED
TIRE TYPE	TL
LI/SS	173 D



DIMENSIONES US STANDARD

CÓDIGO USA	94506293	RC (IN)	179.1
SW (IN)	27.0	RIM REC	AG 20.00
OD (IN)	58.5	RIM ALT	AG 24.00
SLR (IN)	26.6	ECE	E11-106R-0010340

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	14	12	20	23	26	29	32	35	38	41
45	4050	4700	5360	6660	7570	8870	9920	10820	11870	13040
40	4440	5160	5870	7310	8310	9740	10890	11890	13040	14330
30	5380	6250	7110	8850	10060	11790	13180	14400	15780	17340
25	6050	7020	7990	9940	11310	13260	14810	16180	17740	19490
15	7020	8160	9290	11550	13140	15400	17220	18790	20610	22640
5	8000	9290	10580	13160	14970	17550	19610	21420	23480	25790

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.